

Linea **IRON 06.3N**



Rettificatrici Schleifmaschinen
Rectifieuses **Grinding machines**

ROSA ERMANDO® CE



Longitudinale rettificabile Longitudinal grinding length - Longueur rectifiable Schleiflänge längs	mm	620
Larghezza rettificabile Cross grinding width - Largeur rectifiable Querchleifbreite	mm	400
Altezza rettificabile con mola nuova Vertical grinding height with new wheel Hauteur verticale rectifiable avec meule neuve Max schleif bare Höhe Senkrecht mit neuen Schleifscheibe	mm	330
Corsa longitudinale Longitudinal travel - Course longitudinal - Längsweg	mm	850
Velocità di traslazione Longitudinal speed - Vitesse longitudinale Längsgeschwindigkeit	m/min	1 - 32
Superficie della tavola porta pezzo Table surface - Surface de table - Tischauflage	mm	600 x 300
Carico ammissibile Admissible weight on the table Charge admissible sur la table Zulässige Tischbelastung	kg	1000
Corsa trasversale Cross travel - Course transversale - Querweg	mm	360
Velocità di traslazione Y Cross speed Y - Vitesse transversale Y Querweggeschwindigkeit Y	m/min	0 - 3,5
Distanza tavola mandrino Distance table to center spindle Distance table à centre de la broce Distance Tisch/Spindelmitte	mm	505
Velocità traslazione Z Vertical speed Z - Vitesse verticale Z Vertikalgeschwindigkeit Z	m/min	2
Potenza motore Power of wheel motor - Puissance de la meule Schleifspindelmotorsleistung	kW	5,5 (S6)
Velocità rotazione Wheel speed - Vitesse de la meule Schleifscheibendrehzahl	rpm	1500
Dimensioni mola Dimensions of grinding wheel Dimensions de la meule Schleifscheibenabmessungen	mm	ø350 x 25 - 50 x ø127
Lunghezza Length - Longueur - Länge	mm	3000
Larghezza Width - Largeur - Breite	mm	2020 + rack
Altezza Height - Hauteur - Höhe	mm	1900
Peso totale senza accessori Weight without optional - Poids sans options Gewicht ohne Zubehör	kg	3500
Pressione acustica (Leq) Noise level - Niveau de bruit - Geräuschniveau	dB	≤76
Potenza installata senza accessori Installed power without optional Puissance installée sans options Install.Leistung ohne Zuberhören	kW	9

Dati e caratteristiche non sono impegnativi e possono essere modificati senza preavviso. Design and specifications are subject to change without notice.
Les données et caractéristiques peuvent être modifiées sans avis. Daten und Merkmale sind unverbindlich und können ohne Vorankündigung geändert werden.

ROSA**ROSA DO BRASIL LTDA.**

Rua Dr. Luiz Arrobas Martins, 486
Vila Friburgo 04784-140
Socorro-Interlagos - SP
Brasil
Tel/Fax +55 11 5686-8805
rosabrasil@uol.com.br

ROSA UCAM
GRINDTECH**ROSA-UCAM GRINDTECH PVT. LTD.**

A-11, 1st Stage 1st Cross,
PEENYA INDUSTRIAL AREA
BANGALORE - 560058 INDIA
Phone: + 91 80 32923466 / 28397895
Fax: +91 80 28397875
sales@rosaucam.com

ROSA ERMANDO**ROSA ERMANDO spa**

20027 Rescaldina (Milano) ITALY via Montelungo, 16 - Tel. +39 0331 576280 - Telefax +39 0331 464027 - rosa@rosa.it - www.rosa.it

